



Swappable Modules

DVBT2

DVBC

HDMI

DVBS/S2

CI

CE Certified



Flexi-MU-R

Code	9001040
Input Voltage	240~90VAC
Power	100W
Chassis Dimension	480mmx 44mm x 425mm (W x H x D), 1 RU
Operating Temperature	°0C~°50C
Storage Temperature	°10-C~°70C
Operating Humidity	<%95
MTBF	≥100,000 hours

6 hot-swappable slots

Dual power supplies - Redundancy

Service level multiplexing

4 x Gigabit RJ45 (embedded) :

- MPEG TS over UDP/RTP multicast/unicast
- SPTS/MPTS
- Max. -128CH inputs and -128CH outputs (altogether)
- Max. 840Mbps effective bandwidth (altogether)

Flexi-MU-M

Code	9001041
Input Voltage	240~90VAC
Power	100W
Chassis Dimension	480mmx 44mm x 425mm (W x H x D), 1 RU
Operating Temperature	°0C~°50C
Storage Temperature	°10-C~°70C
Operating Humidity	<%95
MTBF	≥100,000 hours

6 hot-swappable slots

Dual power supplies - Redundancy

Service level multiplexing

4 x Gigabit RJ45 (embedded) :

- MPEG TS over UDP/RTP multicast/unicast
- SPTS/MPTS
- Max. -128CH inputs and -128CH outputs (altogether)
- Max. 840Mbps effective bandwidth (altogether)

Embedded Modulation Card DVBC/DVBT

Flexi-MU

Code	9001039
Input Voltage	240~90VAC
Power	100W
Chassis Dimension	480mmx 44mm x 425mm (W x H x D), 1 RU
Operating Temperature	°0C~°50C
Storage Temperature	°10-C~°70C
Operating Humidity	<%95
MTBF	≥100,000 hours

6 hot-swappable slots

Dual power supplies - Redundancy

Service level multiplexing

4 x Gigabit RJ45 (embedded) :

- MPEG TS over UDP/RTP multicast/unicast
- SPTS/MPTS
- Max. -128CH inputs and -128CH outputs (altogether)
- Max. 840Mbps effective bandwidth (altogether)

